

GE

Energy Connections

Model 182

Current Transformer Window Diameter 1.25"

Application

Relaying and metering.

Frequency

50-400 Hz.

Insulation Level

600 Volt, 10 kV BIL full wave.

Terminals are brass studs No. 8-32 with one flatwasher, lockwasher, and regular nut.

Order mounting bracket kit 0221B00777 separately.

Approximate weight 5.5 lbs.



REGULATORY AGENCY APPROVALS




Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1

Model 182

Catalog Number	Current Ratio	Relay Class	ANSI Metering Class at 60 HZ					Secondary Winding Resistance (Ω @ 75 °C)	Continuous Thermal Rating Factor	
			B0.1	B0.2	B0.5	B0.9	B1.8		@ 30 °C	@ 55 °C
182-101	100:5	—	0.6	0.6	2.4	4.8	—	0.034	2.0	2.0
182-151	150:5	C10	0.3	0.3	1.2	1.2	2.4	0.051	2.0	2.0
182-201	200:5	C10	0.3	0.3	0.6	1.2	2.4	0.068	2.0	2.0
182-251	250:5	C20	0.3	0.3	0.3	0.6	1.2	0.085	2.0	1.5
182-301	300:5	C20	0.3	0.3	0.3	0.3	0.6	0.102	2.0	1.5
182-401	400:5	C20	0.3	0.3	0.3	0.3	0.6	0.189	1.5	1.0



Model 182



GEGridSolutions.com

Grid-AIS-L4-ITL_Model_182-1272-2017_06-EN. © Copyright 2017. General Electric Company and Instrument Transformers LLC reserve the right to change specifications of described products at any time without notice and without obligation to notify any person of such changes.

Worldwide Contact Center

Web: www.GEGridSolutions.com/contact

Phone: +44 (0) 1785 250 070

USA and Canada: +1 (0) 800 547 8629

Europe, Middle East and Africa: +34 (0) 94 485 88 00

