Machine Tool Relays

Product Selection

When Ordering, Specify

- Catalog number of basic relay with 120/60, 110/50 AC coil from AR/ARD Relays table.
- If a coil voltage other than listed is required, select the suffix code from the Coil Voltage table below and substitute it for the last letter in the catalog number. Example: AR64**V** for a 110/60 AC coil.

AR/ARD Relays

3

AR/ARD Relays



Contact			AR 600 Vac Relays 120/60, 110/50 AC Coil Catalog Number	ARD 600 Vdc Relays 120 DC Coil Catalog Number
NO	NC	Blank Cavities		
0	0	4	AR4A	ARD4S
2	0	2	AR420A	ARD420S
4	0	0	AR440A	ARD440S
0	0	6	AR6A	ARD6S
4	0	2	AR640A	_
6	0	0	AR660A	ARD660S
6	0	2	AR860A	ARD860S ²
8	0	0	AR880A	ARD880S
10	0	0	AR10100A	ARD10100S
	NO 2 4 0 4 6 6 8	NO NC 0 0 2 0 4 0 0 0 4 0 6 0 8 0	NO NC Blank Cavities 0 0 4 2 0 2 4 0 0 0 0 6 4 0 2 6 0 0 6 0 2 8 0 0	Contact 120/60, 110/50 AC Coil NO NC Blank Cavities Catalog Number 0 0 4 AR4A 2 0 2 AR420A 4 0 0 AR440A 0 0 6 AR6A 4 0 2 AR640A 6 0 0 AR660A 6 0 2 AR860A 8 0 0 AR880A

Coil Voltage

AR Coils

Volts AC	Hz	Suffix Code
12	60	F
24	60	I
48	60	G
110	60	V
110/120	50/60	Α
208	60	В
220/240	50/60	W
277	60	C
380/440	50/60	H
440/480	50/60	X
550	60	D
550/600	50/60	E

Volts DC	Suffix Code
12	D
24	L
48	М
95	В
120	S
130	U
240	Т

ARD Coils

Contact Cartridges-600V

Standard Contact Cartridge Catalog Number ⁽)	Overlap Contact Cartridge Catalog Number [@]
ARC	AROC
ARCR	AROCR
ARDC	ARDOC
ARDCR	ARDOCR
	ARC ARC ARC ARC

Notes

Will not accept top-mounted latch or timers.

Contact Customer Support Center for availability.

(3) Standard cartridges are sold in cartons of four cartridges. Catalog number is for single cartridge.

 $\circledast\,$ Overlap contact cartridges are sold in sets of two cartridges. Catalog number is for sets of two.