

S505SC

5 x 20 mm Time-delay, axial lead ceramic tube fuses



Product description

- Time-delay, high breaking capacity
- Designed to IEC 60127-2
- Nickel-plated brass end cap construction
- 5 x 20mm physical size
- Halogen free, lead free, RoHS compliant

Applications

Primary circuit protection:

- Power supplies
- LED lighting
- LED/LCD televisions
- Appliances and white goods
- Printers

Agency information

- cURus Recognition file number: E19180, Guide JDYX2/JDYX8
- SEMKO: File 1219335, 1310139
- VDE: File 40024252, 40037710 (1-8A)
- BSI: File KM55676
- IMQ: File CA03.00529
- PSE/JET: JET1641-31003-1010, JET1641-31003-2002, JET7042-31003-2001
- CQC: 12012079823, 13012103317
- KC-Mark: File SU05011-12003, SU05011-12004, SU05011-12005A; SU05030-13003A, SU05030-13004, SU05030-13005
- TUV: J50233218

Ordering

- Specify packaging prefix and part number as shown

Packaging prefix	Part number
BK/	S505SC-1-R

Packaging prefixes

- BK/ 20 parts in a carrier, 5 carriers in a box
- TR2/1500 parts per reel, tape width 52mm
- TR3/1500 parts per reel, tape width 54mm

Electrical characteristics

I_n	$1.5I_n$ min minute	$2.1I_n$ max minute	$2.75I_n$ min ms	max s	$4I_n$ min ms	max s	$10I_n$ min ms	max ms
1A-3.15A	60	30	750	80	95	5	10	150
4A-6.3A	60	30	750	80	150	5	10	150
8A-10A	30	30	750	80	150	5	10	150

Product specifications


Part number ⁵	Voltage rating AC	Interrupting rating at rated voltage (50 Hz) AC ¹ (amps)	Typical DC cold resistance (Ω) ²	Typical pre-arcing I^2t (A^2s) ³	Typical voltage drop (mV) ⁴	IMQ	VDE	SEMKO	cURus	PSE/JET	KC	BSI	TUV
S505SC-1-R	250	1500	0.169	1.38	180	x	x	x	x	x	x	x	x
S505SC-1.25-R	250	1500	0.108	2.14	151	x	x	x	x	x	x	x	x
S505SC-1.6-R	250	1500	0.070	7.35	130	x	x	x	x	x	x	x	x
S505SC-2-R	250	1500	0.055	9.83	123.5	x	x	x	x	x	x	x	x
S505SC-2.5-R	250	1500	0.040	19.9	119	x	x	x	x	x	x	x	x
S505SC-3.15-R	250	1500	0.031	40.4	110	x	x	x	x	x	x	x	x
S505SC-4-R	250	1500	0.018	41.0	89.8	x	x	x	x	x	x	x	x
S505SC-5-R	250	1500	0.013	71.2	88	x	x	x	x	x	x	x	x
S505SC-6.3-R	250	1500	0.010	152	72.5	x	x	x	x	x	x	x	x
S505SC-8-R	250	1500	0.007	237	82.5	x	x	x	x	x	x	x	x
S505SC-10-R	250	1500	0.005	353	70	x		x	x	x	x	x	x

1 Interrupting ratings 1A to 10A were measured at 70% to 80% PF on AC.
2 Typical DC cold resistance measured at <10% of rated current .
3. Typical I^2t value is measured at 10 times the rated current under DC.


4. Typical voltage drop is measured at 20°C ambient temperature at rated current .
5. Part number definition: S505SC-xxx-R
S505 = Product code
SC = Single cap
xxx = Ampere rating
-R = RoHS compliant

Dimensions—mm


A
BK: 38.1±0.38
TR2: 15.0 typ
TR3: 16.0 typ




Time vs. current curve



I²t vs. time curve




Temperature derating curve



Environmental data

Operating temperature: -55°C to 125°C (with derating)

Wave solder profile



Reference EN 61760-1:2006

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat	• Temperature min. (T_{smin})	100°C
	• Temperature typ. (T_{styp})	120°C
	• Temperature max. (T_{smax})	130°C
	• Time (T_{smin} to T_{smax}) (t_s)	70 seconds
Δ preheat to max Temperature	150°C max.	150°C max.
Peak temperature (T_p)*	235°C – 260°C	250°C – 260°C
Time at peak temperature (t_p)	10 seconds max 5 seconds max each wave	10 seconds max 5 seconds max each wave
Ramp-down rate	~ 2 K/s min ~3.5 K/s typ ~5 K/s max	~ 2 K/s min ~3.5 K/s typ ~5 K/s max
Time 25°C to 25°C	4 minutes	4 minutes

Manual solder

350°C, 4-5 seconds. (by soldering iron), generally manual, hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/elx

© 2015 Eaton
All Rights Reserved
Printed in USA
Publication No. 10132 BU-SB15187
May 2015

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Eaton:

[BK-S505SC-10-R](#) [BK-S505SC-5-R](#) [TR2-S505SC-4-R](#) [TR3-S505SC-3-15-R](#) [TR3-S505SC-4-R](#) [TR2-S505SC-6-3-R](#)
[TR3-S505SC-2.5-R](#) [BK-S505SC-6-3-R](#) [TR3-S505SC-1.6-R](#) [TR3-S505SC-8-R](#) [TR2-S505SC-2-R](#) [BK-S505SC-4-R](#)
[BK-S505SC-2-R](#) [TR2-S505SC-1.25-R](#) [TR2-S505SC-1-R](#) [TR3-S505SC-2-R](#) [TR3-S505SC-6-3-R](#) [TR2-S505SC-3-15-R](#)
[BK-S505SC-2-5-R](#) [BK-S505SC-8-R](#) [TR3-S505SC-1-R](#) [TR3-S505SC-1.25-R](#) [TR2-S505SC-5-R](#) [BK-S505SC-1-6-R](#)
[BK-S505SC-1-25-R](#) [TR3-S505SC-10-R](#) [TR2-S505SC-2.5-R](#) [BK-S505SC-1-R](#) [TR2-S505SC-10-R](#) [TR2-S505SC-1.6-R](#)
[TR2-S505SC-8-R](#) [BK-S505SC-3-15-R](#) [TR3-S505SC-5-R](#)